

SC8701Q High Efficiency, Synchronous Buck-Boost Controller

1 Description

The SC8701Q is a synchronous 4-switch buck-boost controller. It can effectively output voltage no matter it is higher, lower or equal to the input voltage.

The SC8701Q supports very wide input and output voltage range. It can support applications from 2.7V to 36V input range and 2V to 36V output range. The driver voltage is set to 10V to fully utilize external MOSFETs for highest efficiency.

The SC8701Q supports input current limit, output current limit and over temperature protections to ensure safety under different abnormal conditions.

The SC8701Q adopts 32 pin QFN 4x4 package.

2 Features


- AEC-Q100 qualified for automotive applications:
 - Temperature grade 1: T_A range: -40°C to $+125^{\circ}\text{C}$
 - HBM ESD classification level H1C
 - CDM ESD classification level C6
- Highly efficient buck-boost operation
- Dynamic adjustable output voltage
- Dynamic adjustable Input and Output current limit
- Wide input voltage range: 2.7 V to 36 V
- Wide output voltage range: 2V to 36V
- Integrated 10V, 2A gate driver
- Adjustable frequency 200kHz to 600kHz
- Under voltage protection
- QFN-32 Package

3 Applications


- Automotive USB Charging
- Car Charger
- Automotive Wireless Charging

4 Device Information


ORDER NUMBER	PACKAGE	BODY SIZE
SC8701QQDER	32 pin QFN	4mm x 4mm x 0.75mm



5 Typical Application Circuit



6 Terminal Configuration and Functions



TERMINAL		I/O	DESCRIPTION
NUMBER	NAME		
1	/CE	I	Chip Logic Enable, CE=Low, chip enable. Internal pull low. Suggest adding a 1~10kΩ resistor if using an IO to control this pin.
2	NC	I	Floating
3	PWM	I	PWM pin accepts square waveform from 20K to 100K. By adjusting duty cycle, output voltage can be adjusted according to needs. When duty=0, output voltage = 1/6 of the preset value by the feedback resistor divider at FB pin. When duty = 100%, output voltage = preset value. $V_{OUT} = V_{OUT_SET} \times (\frac{1}{6} + \frac{5}{6} \times D)$
4	PG	O	Open drain, active high when V_{OUT} is within 90% to 110% * V_{OUT} target.
5	IPWM	I	IPWM pin is used together with ITUNE pin to adjust the current limit value of either ILIM1 or ILIM2. The ITUNE pin is used to select the control object between ILIM1 and ILIM2, and IPWM signal is to adjust the limit value. IPWM pin accepts PWM waveform from 20kHz to 100kHz, and the current limit value is proportional to its duty cycle. For example, if ITUNE pin selects ILIM1, then the input current limit is set by: $I_{IN} = I_{LIM1_SET} \times D$ In the equation above, I_{LIM1_SET} is the current limit value set by the resistor at ILIM1 pin, D is the duty cycle of the IPWM signal. Similarly, if ITUNE pin selects ILIM2, then the output current limit is set by: $I_{OUT} = I_{LIM2_SET} \times D$
6	ITUNE	IO	ITUNE pin selects the IPWM control object between ILIM1 and ILIM2. If ILIM1 current limit needs to be controlled, connect the ILIM1 resistor between ILIM1 pin and ITUNE pin. If ILIM2 current limit is to be controlled, connect the ILIM2 resistor between ILIM2 pin and ITUNE pin. Only one current limit can be selected by ITUNE pin. If IPWM function is not needed, leave ITUNE pin and IPWM pin floating, and connect the ILIMx resistor from the ILIMx pin to AGND accordingly.

7	NC	I	Floating.
8	DT	I	Dead Time selection. Short to ground: 20ns; 68kΩ: 40ns; 270kΩ: 60ns; Open: 80ns
9	NC	I	Floating
10	FREQ	I	Frequency selection Short to ground: 200kHz; 68kΩ: 400kHz; Open: 600kHz
11	ILIM1	I	<p>Connect a resistor to set the current limit value of input current.</p> $I_{LIM1_SET} = \frac{V_{REF}}{R_{ILIM1}} \times \frac{R_{SS1}}{R_{SNS1}}$ <p>V_{REF} is the internal reference voltage 1.21V.</p> <p>R_{LIM1} is the resistor from ILIM1 to ground or to ITUNE.</p> <p>R_{SNS1} is the current sense resistor. Recommended 5mΩ-20mΩ, typical 10mΩ.</p> <p>R_{SS1} are the resistors connected to SNS1P, SNS1N. The two resistors must be equal and the recommended value is 1kΩ.</p> <p>A 2.2nF capacitor to ground is needed to bypass noise. If IPWM function is applied to ILIM1, increase the capacitor value to 10nF. If current limiting function is not needed, please short ILIM1 to ground.</p>
12	ILIM2	I	<p>Connect a resistor to set the current limit value of output current.</p> $I_{LIM2_SET} = \frac{V_{REF}}{R_{ILIM2}} \times \frac{R_{SS2}}{R_{SNS2}}$ <p>V_{REF} is the internal reference voltage 1.21V;</p> <p>R_{LIM2} is the resistor from ILIM2 to ground or to ITUNE;</p> <p>R_{SNS2} is current sensing resistor. Recommended 5mΩ-20mΩ, typical 10mΩ;</p> <p>R_{SS2} are the resistors connected to SNS2P, SNS2N. The two resistors must be equal, and the recommended value is 1kΩ.</p> <p>A 2.2nF capacitor to ground is needed to bypass noise. If IPWM function is applied to ILIM2, increase the capacitor value to 10nF. If current limiting function is not needed, please short ILIM2 to ground.</p>
13	NC	I	Floating
14	AGND	IO	Analog Ground
15	COMP	O	Compensation for the control loop.
16	FB	I	<p>Feedback for output voltage.</p> $V_{OUT} = V_{REF} \times \left(1 + \frac{R_{UP}}{R_{DOWN}}\right)$ <p>V_{REF} equals to 1.22V. R_{UP} and R_{DOWN} are the value of voltage divider.</p>
17	SNS2N	I	Negative input of current sense amplifier. Connect an external current sense resistor between SNS2P and SNS2N. Current flows from SNS2P to SNS2N.

18	SNS2P	I	Positive input of current sense amplifier. Connect an external current sense resistor between SNS2P and SNS2N. Current flows from SNS2P to SNS2N.
19	VOUT	I	Output node of the converter.
20	BT2	PWR	Connect a capacitor between BT2 pin and SW2 pin to bootstrap a voltage to provide the bias voltage for high side MOSFET gate driver2.
21	HD2	PWR	High side MOSFET gate driver2 output
22	SW2	PWR	Switching Node 2
23	LD2	PWR	Low side MOSFET gate driver2 output
24	VCC	PWR	Output of internal regulator to provide 10V voltage for the bias voltage of internal gate drivers. Connect a 1 μ F ceramic capacitor from V _{CC} to PGND pin.
25	PGND	PWR	Power Ground
26	LD1	PWR	Low side MOSFET gate driver1 output
27	SW1	PWR	Switching Node 1
28	HD1	PWR	High side MOSFET gate driver1 output
29	BT1	PWR	Connect a capacitor between BT1 pin and SW1 pin to bootstrap a voltage to provide the bias voltage for high side MOSFET gate driver1.
30	VIN	I	Input node of the converter
31	SNS1N	I	Negative input of current sense amplifier. Connect an external current sense resistor between SNS1P and SNS1N. Current flows from SNS1P to SNS1N.
32	SNS1P	I	Positive input of current sense amplifier. Connect an external current sense resistor between SNS1P and SNS1N. Current flows from SNS1P to SNS1N.
	Thermal Pad		For thermal dissipation. Connect to AGND or PGND.

7 Specifications

7.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted) ⁽¹⁾

		MIN	MAX	UNIT
Voltage range at terminals ⁽²⁾	VIN, VOUT, SNS1P, SNS1N, SNS2P, SNS2N, /CE	-0.3	42	V
	SW1, SW2 ⁽²⁾	-1	42	V
	VCC, PG, PWM, IPWM ⁽²⁾	-0.3	20	V
	FREQ, ILIM1, ILIM2, COMP, DT, FB, ITUNE	-0.3	5.5	V
	LD1, LD2	-0.3	12	V
	BT1, HD1 to SW1	-0.3	12	V
	BT2, HD2 to SW2	-0.3	12	V
	BT1, BT2	-0.3	50	V
Temperature Range	Operating Junction, T _J ⁽³⁾	-40	150	°C
	Storage temperature range, T _{stg}	-65	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values are with respect to network ground terminal.
- (3) Operating at junction temperatures greater than 125°C, although possible, degrades the lifetime of the device.

7.2 Thermal Information

THERMAL RESISTANCE ⁽¹⁾		QFN-32 (4mm x 4mm)	UNIT
Θ _{JA}	Junction to ambient thermal resistance	35	°C/W
Θ _{JC}	Junction to case resistance	7	°C/W

- (1) Measured on JESD51-7, 4-layer PCB.

7.3 Handling Ratings

PARAMETER	DEFINITION	MIN	MAX	UNIT
ESD ⁽¹⁾	Human body model (HBM) ESD stress voltage ⁽²⁾	-1	1	kV
	Charged device model (CDM) ESD stress voltage ⁽³⁾	-1000	1000	V

- (1) Electrostatic discharge (ESD) to measure device sensitivity and immunity to damage caused by assembly line electrostatic discharges into the device.
- (2) Level listed above is the passing level per ANSI, ESDA, and JEDEC JS-001. JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (3) Level listed above is the passing level per EIA-JEDEC JESD22-C101. JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

7.4 Recommended Operating Conditions

Over the recommended operating temperature range of -40 °C to 125 °C (unless otherwise noted) ⁽¹⁾

		MIN	TYP	MAX	UNIT
V _{IN}	Input voltage range	2.7		36	V
V _{OUT}	Output voltage range	2		36	V
C _{IN}	Input Capacitance	30			μF

C _{OUT}	Output capacitance	30			μF
L	Inductance	2.2		10	μH
R _{SNS1/2}	Current Sensing Resistor	5		20	mΩ
f _{SW}	Operating frequency range	200		600	kHz
f _{PWM} , f _{IPWM}	PWM signal frequency range	20		100	kHz
D _{PWM} , D _{IPWM}	PWM signal duty cycle range	0		100	%
T _J	Operating junction temperature	-40		125	°C

(1) Recommended operating conditions indicate conditions for which the device is intended to be functional, but do not ensure specific performance limits. For ensured specifications, see Section 7.5

7.5 Electrical Characteristic


T_j = 25°C and V_{IN} = 12V, V_{OUT} = 5V, R_{SS1} = R_{SS2} = 1kΩ unless otherwise noted.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
SUPPLY VOLTAGE (VIN, VOUT)						
VIN	Operating voltage		2.7		36	V
VOUT	Operating voltage		2		36	V
VUVLO	Input under-voltage lockout threshold	Rising edge		2.6	2.7	V
		Hysteresis		160		mV
IQ	Standby current into VIN or VOUT pin (whichever is higher)	/CE = low, controller non-switching	0.7	2		mA
ISD	Shutdown current into VIN or VOUT pin (which is higher)	/CE = high	6	10		μA
	Shutdown current into VIN or VOUT pin (which is lower)	/CE = high		2		μA
VCC AND DIRVER						
VCC	VCC clamp voltage		9.4	10	10.6	V
IVCC_LIM	VCC current limit	VCC = 2V ~10V,	50	75	100	mA
RHVx_pu	High side driver pull up resistor			1.5		Ω
RHVx_pd	High side driver pull down resistor			1		Ω
RLVx_pu	Low side driver pull up resistor			1.5		Ω
RLVx_pd	Low side driver pull down resistor			1		Ω
ERROR AMPLIFIER						
VFB_REF	FB reference voltage		1.214	1.22	1.226	V
VILIMx_REF	ILIMx reference voltage	Tj= -40°C ~125°C	1.17	1.212	1.24	V
GmEA	Error amplifier gm			0.16		mS
ROUT	Error amplifier output resistance ⁽¹⁾			20		MΩ
IBIAS(FBx)	FBx pin input bias current	FBx in regulation			100	nA
CURRENT LIMIT						
ILIMx	ILIMx current limit accuracy	IIN_LIM RSNS1 ≥ 30 mV IOUT_LIM RSNS2 ≥ 30 mV	-10%		10%	
SWITCHING FREQUENCY						
fSW	Switching frequency	RFREQ = 0Ω, Tj= -40°C ~125°C	180	220	250	kHz
		RFREQ = 68kΩ (±10%), Tj= -40°C ~125°C	360	420	490	kHz
		RFREQ = 270kΩ (±10%), Tj= -40°C ~125°C	540	600	660	kHz
INDICATION						
tPG_deglitch	PG deglitch time	fsw = 200kHz	27	38.5	50	ms
ISINK_PG	PG sink current	VPG = 0.4 V	3.6	4.1	4.6	mA
VOUT_PG	VOUT power good threshold	High limit falling edge (PG from low to high)	105%	110%	115%	
		High limit hysteresis (PG from high to low)		5%		
		Low limit rising edge (PG from low to high)	85%	90%	95%	

		Low limit hysteresis (PG from high to low)	5%	
LOGIC CONTROL				
R _{PD}	/CE internal pull-down resistor		1	MΩ
	PWM pin internal pull-down resistor		0.5	MΩ
	IPWM pin internal pull-down resistor		1	MΩ
V _{IL}	/CE, PWM, IPWM input low voltage		0.4	V
V _{IH}	/CE, PWM, IPWM input high voltage		1.2	V
Soft Start				
t _{SS}	Internal soft-start time	From /CE low to 90% V _{OUT}	8 15	mS
THERMAL SHUTDOWN				
T _{SD}	Thermal shutdown temperature ⁽¹⁾		165	°C
	Thermal shutdown hysteresis ⁽¹⁾		15	°C

(1) Guarantee by design

8 Functional Block



9 Detailed Description

The SC8701 is a synchronous four-switch buck-boost controller with a wide input/output voltage range. The SC8701Q regulates the output at, above, below the input voltage.

The SC8701Q features automatic buck, boost mode smooth transition and maximum input and output current limit capability using additional resistors. In addition, the SC8701Q features output voltage dynamic change, input/output current limit dynamic change, and power MOSFETs dead time control.

9.1 Feature Description

9.1.1 Chip Enable (/CE)

The SC8701Q turns on/off by /CE signal. When /CE input is "L", the SC8701Q is turned on; when /CE input is "H", the SC8701Q is turned off. Suggest to add a 1~10kΩ resistor if using an GPIO to control it.

9.1.2 V_{OUT} voltage setting (FB)

The V_{OUT} voltage is set by external resistor divider at FB pin and is calculated as:

$$V_{OUT} = V_{FB_REF} \times \left(1 + \frac{R_{UP}}{R_{DOWN}}\right)$$

Where:

V_{FB_REF} = Internal reference voltage 1.22V

R_{UP} and R_{DOWN} = Resistor divider at FB connected to V_{OUT} and AGND.

9.1.3 Output voltage POWER GOOD indicator (PG)

The PG signal indicates V_{OUT} voltage status.

If V_{OUT} voltage remains in between 90% ~ 110% of programmed voltage, PG pin becomes high impedance and due to the output pull-up resistor, PG out becomes "H" to indicate the output voltage is good.

If V_{OUT} is out of normal voltage range, PG out becomes "L".

If power good indication is not required, leave PG pin floating.

9.1.4 Real-time output voltage control (PWM)

The SC8701Q supports V_{OUT} voltage change by PWM signal at PWM pin.

The PWM pin accepts a PWM signal in the range of 20kHz to 100kHz, and its duty cycle can adjust the V_{OUT} voltage. V_{OUT} output voltage is calculated as:

$$V_{OUT} = V_{OUT_SET} \times \left(\frac{1}{6} + \frac{5}{6} \times D\right)$$

Where;

V_{OUT_SET} = V_{OUT} voltage which is set by FB resistor divider;

D = Duty cycle of PWM signal.

The relationship between V_{OUT} voltage and D is showed in Figure 1




Figure 1 V_{OUT} voltage vs PWM duty cycle.

If PWM input signal is logic high, it means 100% of duty cycle, then the output voltage become the set value by FB1 resistor divider.

If PWM input signal is logic low, it means 0% of duty cycle, then the output voltage become the 1/6 of the set value.

If PWM pin is left floating, due to the IC internal pull down circuit at PWM pin, V_{OUT} voltage becomes the 1/6 of programmed voltage.

If real-time output voltage control is not required, connect PWM pin to V_{CC} pin.

9.1.5 Input/output current setting (ILIMx)

The SC8701Q can adjust the current limit of both input side and output side by resistors at ILIM1 and ILIM2 pins.

Control Pins	Description
ILM1	Set the input current limit (I _{IN_LIM})
ILM2	Set the output current limit (I _{OUT_LIM})

The SC8701Q senses the input and output current by monitoring R_{SNS1} and R_{SNS2} respectively as below figure shows.




Figure 3 Input/output current monitoring circuit

R_{SNSx} is the current sense resistor (x means 1 or 2) at input/output. The SC8701Q monitors the voltage across the sense resistors R_{SNSx} through R_{SSx} and $R_{SSx'}$ and calculates the input and output current. C_{SSx} is the filter capacitor and typically 47pF is sufficient.

The ILIMx pin is used to set the current limit. Connect the R_{ILIMx} resistor between ILIMx pin and GND (or ITUNE pin if IPWM function is used).

The current limit is calculated as:

$$I_{IN_LIM} = \frac{V_{LIM_REF}}{R_{ILIM1}} \times \frac{R_{SS1}}{R_{SNS1}}$$

$$I_{OUT_LIM} = \frac{V_{LIM_REF}}{R_{ILIM2}} \times \frac{R_{SS2}}{R_{SNS2}}$$

Where:

V_{LIM_REF} = Internal reference voltage 1.21V.

R_{ILIMx} = Resistors at ILIMx pin.

R_{SNSx} = Current sense resistors.

R_{SSx} = Resistors between current sense resistor and the SC8701Q pins (SNSxP, SNSxN).

R_{SNS1} should be placed between MOSFET and input capacitor. R_{SNS2} can be placed either between the MOSFET and output capacitor or behind the output capacitor.

R_{SS1} and $R_{SS1'}$ should have the same value; R_{SS2} and $R_{SS2'}$ also the same. Typically 1kΩ resistor is used.

If R_{SNSx} is changed, $R_{SSx}/R_{SSx'}$ values need to be adjusted accordingly with below calculation:

$$\frac{R_{SNSx}}{R_{SSx}} = \frac{10\text{ m}\Omega}{1\text{ k}\Omega}$$

For example, If R_{SNSx} is 20mΩ, then $R_{SSx}/R_{SSx'}$ should be 2kΩ;

if R_{SNSx} is 5mΩ, then $R_{SSx}/R_{SSx'}$ should be 500Ω.

If both V_{IN} and V_{OUT} current limits are programmed, the SC8701Q controls the current which reaches its current limit first.

If the input/output current limit is not required, connect ILIM1/ILIM2 pin to GND.

9.1.6 Real-Time current control (IPWM)

The SC8701Q can control the input/output current dynamically by applying a PWM signal to IPWM pin.

The IPWM signal should be in the range of 20kHz ~ 100kHz, and the input/output current is proportional to its duty cycle as:

$$I_{LIMx} = I_{LIMx_SET} \times D$$

Where:

$I_{LIMx_SET} = I_{LIMx}$ Input or output current limit value (x=1: input, x=2: output).

D = IPWM duty cycle.

I_{LIMx} = Target current limit of input/output current.

ITUNE pin selects the target which is controlled by IPWM. If input current should be controlled, the resistor at ILIM1 should be connected between ILIM1 and ITUNE pins; If output current should be controlled, the resistor at ILIM2 should be connected between ILIM2 and ITUNE pins.

Only one target can be selected by ITUNE pin.

Refer to Figure 2. IPWM real-time input/output current control.



a. IPWM controls input current, $ILIM1 = ILIM1_set \times D$, as aboveb. IPWM controls output current, $ILIM2 = ILIM2_set \times D$, as above

Figure 2. IPWM real-time input/output current control.

When the IPWM signal is logic high, which means the duty

cycle is 100%, the current limit is then the ILIMx set value.

For the ILIMx pin, which is controlled by IPWM signal, its filter capacitor should still be connected to ground. If the IPWM frequency is low, higher capacitance should be applied. For example, 22nF capacitor is suggested for 20kHz frequency.

If real-time current control is not required, connect ILIMx resistor to GND and float IPWM and ITUNE pins.

Do not leave IPWM pin float if the ITUNE pin is connected to one ILIMx resistor; otherwise, the SC8701Q cannot operate normally.

It is not allowed to set any of the current limits to 0A. Keep the minimum current limit above 0.3A.

9.1.7 Dead time setting (DT)

The one of four dead times is selectable by resistor value at DT pin:

DT resistor	Dead time
0Ω	20ns
68kΩ (±10%)	40ns
270kΩ (±10%)	60ns
Open	80ns

The accuracy of the resistor at DT is allowed ±10%. DT does not support the real-time change and new resistor value change will be applied in next turn on.

When driving large power MOSFET with high C_{iss} value or adding driver resistors at LDx or HDx to adjust the MOSFET turning on/off time, it is suggested to check and change the dead time to prevent MOSFET shoot-through.

9.1.8 Switching frequency setting (FREQ)

The one of three-switching frequency is selectable by resistor value at FREQ pin:

FREQ resistor	Switching frequency f_{sw}
0Ω	200kHz
68kΩ (±10%)	400kHz
Open	600kHz

The accuracy of the resistor at FREQ is allowed ±10%. The real-time switching frequency change is not valid and new resistor value change will be applied in next turn on.

9.1.9 Feedback compensation (COMP)

The feedback loop can be compensated by adjusting the external components to the COMP pin. Typically, the values in Figure 4 are used. If faster loop response is required, user can increase the resistor to like 10kΩ or 20kΩ. After changing the compensation, check and make sure the loop is stable under the application operation conditions.




Figure 4 Feedback loop compensation setting

9.1.10 V_{CC} driver voltage

The SC8701Q generates driver voltage V_{CC} internally. The V_{CC} is selected higher voltage between V_{IN} and V_{OUT} and clamped to 10V if it is higher than 10V.

The driving signal LDx to drive low side MOSFET (Q2 and Q3) is directly supplied from V_{CC} ; the driving signal HDx to drive high side MOSFET (Q1 and Q4) is supplied from the diode in between V_{CC} to BTx pin, which is generated by bootstrap circuit with bootstrap capacitor between BTx and SWx.

10 Application Information

10.1 Input and output capacitor selection

The switching frequency of the SC8701Q is in the range of 200kHz ~ 600kHz. Since MLCC ceramic capacitor has good high frequency filtering with low ESR, above 60μF X5R or X7R capacitors with higher voltage rating than operating voltage with margin is recommended. For example, if the highest operating V_{IN} or V_{OUT} voltage is 12V, select at least 16V capacitor and to secure enough margin, 25V voltage rating capacitor is recommended.

The high capacitance electrolytic capacitor and tantalum capacitor can be used for stable input and output, but capacitor voltage rating should be higher than the highest operating voltage. When the tantalum capacitor is used, at least 1μF ceramic capacitor is placed in parallel. If the electrolytic capacitor is used, much more ceramic capacitors are required. For example, if a 47μF electrolytic capacitor is used, the ceramic capacitors' capacitance is allowed to reduce to 30μF ~ 40μF. Even higher capacitance electrolytic capacitor is used, at least 20μF ceramic capacitor is required.

10.2 Inductor selection

For the SC8701Q system stability, the inductance of 2.2μH ~ 10 μH inductor is required. High inductance (4.7μH ~ 10μH) is used in the system where the input voltage and output voltage difference are big, such as 5V V_{IN} and 20V V_{OUT} or the switching frequency is low; Low inductance (2.2μH) is used in the system which the input voltage and output voltage difference is small but high current is required. Typically, 3.3μH inductor is recommended. The inductance can be adjusted for high efficiency and optimization in application.

The inductor DC resistance value (DCR) affects the conduction loss of switching regulator, so around 10mΩ DCR is recommended for the first selection. If the power is relatively small, high DCR inductor can be selected. But if switch current is high, just like around 10A, then select the lowest DCR inductor as much as possible because 10mΩ DCR also causes 1W power loss.

The inductor saturation current I_{SAT} should be higher than input / output current with sufficient margin.

10.3 Current sense resistor

The RSNS1 and RSNS2 are current sense resistors and 5mΩ ~ 20mΩ resistor value is recommended.

Higher resistor value leads to higher current limit accuracy but using higher resistor value in high current application causes

higher conduction loss. Typically, 10mΩ is recommended. Resistor value can be adjusted depending on current limit and target power efficiency. If R_{SNSx} valued is adjusted, related R_{SSx} value should be adjusted simultaneously.

Please refer to 8.1.5 Input/output current setting (ILIMx) for proper R_{SNSx} and R_{SSx} values. The resistor power rating and temperature coefficient should also be considered. The power dissipation is roughly calculated as $P=I^2R$, and I is the highest current flowing through the resistor. The resistor power rating should be higher than roughly calculated power dissipation. The resistor value can be varied if the temperature increased, and the variation is decided by temperature coefficient along with temperature change. If high accuracy of current limit is required, select lower temperature coefficient resistor as much as possible.

10.4 MOSFET selection

The SC8701Q is a synchronous 4-switch buck-boost controller and it requires 4 NMOS for power switching circuit.

The V_{DS} of MOSFET should be higher than the highest operating voltage with enough margin (recommend more than 10V higher). For example, if the highest operating voltage is 20V, at least 30V rated V_{DS} MOSFET should be selected; If the highest operating voltage is 24V, 40V V_{DS} voltage rating should be selected.

In the application, if the input and output voltage are higher than 10V, driver circuit voltage can reach 10V, and V_{GS} voltage rating of MOSFET should be selected higher than ±10V.

Considering PCB parasitic parameters during operation, driver voltage can be higher than V_{CC} due to transient overshoot, and ±20V V_{GS} is recommended to secure sufficient margin.

The MOSFET current I_D should be higher than the highest input and output current with enough margin.

To ensure the sufficient current capability in relatively high temperature circumstance, the current rate at $T_A=70^\circ\text{C}$ or $T_C = 100^\circ\text{C}$ should be considered. In addition, the power dissipation value P_D should also be considered, and higher P_D is better in applications. Make sure that MOSFET power consumption must not exceed P_D value.

The MOSFET $R_{DS(ON)}$ and input capacitor C_{ISS} impact power efficiency directly. Typically, lower $R_{DS(ON)}$ MOSFET has higher C_{ISS} . The $R_{DS(ON)}$ is related to conduction loss. Higher $R_{DS(ON)}$ results in higher conduction loss, thus lower efficiency, and higher thermal dissipation; the C_{ISS} is related to MOSFET switch on/off time, and longer on/off time results in higher switching loss and lower efficiency. The proper MOSFET should be selected based on tradeoff between the $R_{DS(ON)}$ and C_{ISS} .

Normally, if the output power is around 20W ~ 30W, the MOSFET with around 10mΩ of $R_{DS(ON)}$ and lower than 1000pF of C_{ISS} is recommended. If the output power is increased, the

MOSFET with lower $R_{DS(ON)}$ and under 2000pF C_{ISS} is recommended. The highest C_{ISS} is suggested not to exceed 3000pF.

If high C_{ISS} MOSFET is selected, the switching on and off time become longer, then the dead time should be adjusted with DT pin to avoid simultaneous turn on for both high side and low side MOSFETs.

10.5 Driver resistor and SWx snubber circuit

For a convenient adjustment of MOSFET switching time and transient overshoot at EMI debugging, recommend adding 0603 series resistor between driver pins (LD1, LD2, HD1, HD2) and MOSFET Gate pins, and add RC snubber (0603) circuit at SW1 and SW2 (refer to Figure 5 Driver resistor and SWx snubber circuit)

The driver resistor should be placed near to MOSFET Gate pin. At first, add 0Ω and adjust the resistor value appropriately within 10Ω . After increasing the driver resistor value, the on

time of high side and low side MOSFET should be monitored. If the dead time is insufficient, adjust dead time accordingly.





Figure 5 Driver resistor and SWx snubber circuit

The RC snubber circuit is required when the overshoot at SWx needs to suppress. Leave RC snubber circuit as NC at the first time

Packaging Information QFN32L (0.75x0.75-0.40)



Package Information

Orderable Device	Package Drawing	Pins	Package Qty	Device Marking
SC8701QQDER	QDE	32	3000	SC8701QQDER